



T-MOD TYPE

ORDERING INFORMATION

Part No.	Description
HC-206-I-U1 (Unshielded)	Splits a 4-pair USOC jack,
HC-206-I-S1 (Shielded)	for Token Ring or voice applications at either jack.





ORDERING INFORMATION

Part No.	Description
HC-206-I-U2 (Unshielded)	Splits a 4-pair T568B jack,
HC-206-I-S2 (Shielded)	for Token Ring or voice applications at either jack.

ORDERING INFORMATION

Part No.	Description
HC-206-I-U3 (Unshielded)	Splits a 4-pair T568A jack,
HC-206-I-S3 (Shielded)	for Token Ring or voice applications at either jack.





ORDERING INFORMATION

Part No.	Description
HC-206-I-U4 (Unshielded)	Splits a 4-pair T568A/ T568B jack,
HC-206-I-S4 (Shielded)	for 10 BASE-T (jack 1) and Token Ring or voice applications (jack 2).

ORDERING INFORMATION

Part No.	Description
HC-206-I-U5 (Unshielded)	Splits a 4-pair T568A/ T568B jack,
HC-206-I-S5 (Shielded)	for 10 BASE-T applications at either jack.



ORDERING INFORMATION

Part No.	Description
HC-206-I-U6 (Unshielded)	Splits a 4-pair T568B jack,
HC-206-I-S6 (Shielded)	for 1,2 or 3 pair voice (jack 1) and 1-pair voice/modem (jack 2).

ORDERING INFORMATION

Part No.	Description
HC-206-I-U7 (Unshielded)	Bridges all jack pairs. Compatible with any jack wiring. Provides an additional 4-pair jack with the same wiring.
HC-206-I-S7 (Shielded)	

